



DUAL OUTPUT OPTION.
ABOVE ITEMS ARE NOT INCLUDED WITH TANK.

PRESSURE TANK SPECIFICATIONS
MAWP 13.1BAR @ 37.8C

| COMPONENT | QTY | SIZE | MATERIAL | NOM.THK | LOCATION |
|--------------|-----|-------------------|-------------|---------|----------|
| LID | 1 | 127mm x 152.4mm | SA240 304-L | 2.18mm | TOP |
| HANDHOLE | 1 | 127mm x 152.4mm | . | . | TOP |
| OUTLET | 1 | 1/2" NPTF | SA479 316-L | 5.23mm | BOTTOM |
| INLET/OUTLET | 1 | 1/4"NPTF | SA479 316-L | 4.36mm | TOP |
| INLET/OUTLET | 1 | 3/8"NPTF | SA479 316-L | 4.36mm | TOP |
| SKIRT | 1 | 304.8mm | SA240 304-L | 4.36mm | BOTTOM |
| BOTTOM HEAD | 1 | 304.8mm | SA240 304-L | 2.08mm | BOTTOM |
| TOP HEAD | 1 | 304.8mm | SA240 304-L | 2.18mm | TOP |
| SHELL | 1 | 304.8mm x 512.8mm | SA240 304-L | 2.67mm | . |

ABOVE ITEMS 7, 8, 11, & 14
ARE NOT INCLUDED WITH TANK

● = CRITICAL SPARE PART
○ = SUGGESTED SPARE PART

| | | | |
|----|-----|--------|-----------------------------|
| 19 | 0/1 | X097 | TEE, 1/2NPTF |
| 18 | 0/2 | X070 | ELBOW, 1/2M-1/2F |
| 17 | 1 | 582-25 | TANK, 25 GALLON |
| 16 | 1 | 582-20 | TANK, 20 GALLON |
| 15 | 1 | 582-16 | TANK, 16 GALLON |
| 14 | 1/2 | 803-13 | QUICK CONNECT MALE, 1/2NPTM |
| 13 | 1 | X081 | 1/2NPT x 6" PIPE, SS |
| 12 | 1 | X032 | ELBOW, 1/2NPTF BRASS |
| 11 | 2/3 | X014 | NIPPLE, 1/2NPT BRASS |
| 10 | 1 | X042 | PLUG, 1/4NPT BRASS |
| 9 | 1 | X043 | PLUG, 3/8NPT BRASS |
| 8 | 1 | 582-08 | SHUT-OFF VALVE |
| 7 | 1 | 600 | FILTER ASSY, SCREEN SIZE? |
| 6 | 1 | 582-06 | AIR PRESSURE REGULATOR |
| 5 | 1 | 582-05 | SAFETY RELIEF VALVE |
| 4 | 1 | 582-04 | ● O-RING, TANK LID |
| 3 | 1 | 582-03 | LID, TANK |
| 2 | 1 | 582-02 | TANK, 12 GALLON |
| 1 | 1 | 582-01 | TANK, 6 GALLON |

| ITEM | QTY | PART NUMBER | SP | DESCRIPTION |
|--|-----|---------------------------|----------------------|--|
| PRESSURE TANK ASSEMBLY (1/2 OUTPUT) | | | | |
| | | APQUIP COMPANY LLC | | 5 Harris Court, Unit Q Monterey, CA 93940 Tel: 831.642.6565 Fax: 831.642.6563 |
| | | | NUMBER 582 | REV B |